

Series 5000B CD

VGS™ Linear Cuttings Drier



The Difference

- *High “G” force*
- *34 ft² screening area*
- *Simple design*
- *Rugged and reliable*
- *High performance*
- *Low maintenance*
- *Quick screen panel changes*
- *Small footprint*
- *No lubrication*
- *Low noise*

VGS Configuration Optional

High “G” force, high volume
Introducing the 5000B CD, RIG OIL LLC’s latest advance in high “G” force, high volume linear cuttings driers. RIG OIL LLC has designed this unit to achieve optimum performance, allowing you to recover up to 80% of the solids currently reporting to your reserve pit. The 5000B CD will recover silts and ultrane sands, provide solids in a consistently stackable and conveyable form and requires no expensive chemicals or polymers. Even in the most challenging applications, the 5000B CD achieves consistently high throughput. Processing rates vary with slurry content, percent solids and viscosity.

Lowest maintenance cost
Simplicity pays o. RIG OIL LLC equipment have the lowest operational and maintenance costs in the industry. Routine maintenance is extremely minimal. Simple visual checks of screen panels, deck rubbers, isolators, and quarterly torque checks of the vibrator motor bolts are all that is required. RIG OIL LLC keeps you on-line for decades of trouble free performance. It’s that simple!



Series 5000B CD

VGS Linear Cuttings Drier

General Specifications

Series:	5000
Model:	B4
Motors:	Two each 1800 rpm exp. proof or non-exp. proof available
Bearings:	Permanently sealed and lubricated
Motion:	Linear, 0.13" A, 4.5 "G", 20 Hz
VGS:	Force adjustable to 7.0 "G" maximum
Screens:	Four each 29" x 42" pretensioned panels with Wedgelok™ fasteners
Screening area:	33.8 sq. ft. [3.14 sq. m.]
Overall dimensions:	129 1/2" L x 67 5/8" W x 52" H

